



KEY FEATURES


- Bottom rolling sliding door with minimal sill recesses.
- Tested for compliance with relevant Australian Standards.
- The extra strong multi-hollow meeting stiles allow large sliding doors to be fabricated in high wind load areas.
- These panels are always fabricated with low bottom rail and rail stiffeners.
- There are a large variety of door combinations (XF, FX, FXXF, XXF, FXX, FXXXXF, FX^XF, FXX^XXF and cavity sliding doors).
- Compatible with Centor SIE roller screens up to 7500mm wide, alternative sliding stacking flydoor system available.
- Bottom rolling doors run on heavy duty double or quad bogey wheel carriages.
- Sub-sills are fitted with integrated co-extruded Santoprene drainage hole cover flap to prevent blow-back.
- Optional AWS Ventient passive ventilation system can be fitted into tubular sub-head on 102mm and 150mm




The 35mm sill is rated at 300Pa water resistance based on tests carried out on a similar door/sill configuration.



This door achieved a high water resistance of 450Pa with 55mm high sill.



Patented moulded nylon turbulence diverters protect the meeting stile junction at sill, guiding air and turbulence away from the inside.



Bottom rolling doors run on heavy duty double or quad bogey wheel carriages

GENERAL

Max Panel Height*
3300mm

Max Panel Width*
2500mm

Max Glass Thickness
24mm

Frame Depth
Various

ENERGY

UW Range
3.0-6.2

SHGC Range
0.15-0.59

WEATHER

Maximum Water
300 Pa. (35mm Sill)

450 Pa. (55mm Sill)

ACOUSTICS

6.38mm Lam
30 (0;-1)

10.38mm Lam
31 (-1;-1)

10.5mm VLam Hush™
33 (0;-2)



*Dimensions subject to individual site conditions.

BAL-40 compliance may limit glass options. Maximum glass size for BAL-40 products is 4.5m2.