



### KEY FEATURES


- A high performance, bottom rolling sliding door with a recessed sill.
- The custom quad rollers are fully adjustable and run on a replaceable, 316 stainless steel insert track.
- Patented moulded nylon turbulence diverters protect the meeting stile junction at sill, guiding air and turbulence away from the inside.
- There are a large variety of door combinations (XF, FX, FXXF, XXF, FXX, FXXXXF, XXXF, FXXX, FXXXXXXF and corner doors).
- We can fit Centor SIE roller screens behind Series 704 sliding doors up to 7400mm wide.
- Square clean lines with soft radius edges on internal meeting stile corners.
- Doors fitted with custom mortice lock at meeting stiles. Lock only accessible from the inside. Slimline stiles possess built-in, full height, finger grip inside and out.




When recessed into the floor, clear glass sight lines can be achieved and the sill can be combined with a FlowTHRU™ drain for the ultimate flush sill transition.



Heavy duty stainless steel rollers run on a stainless steel insert track for smooth and long lasting operation.



The stiles and jamb are fully recessed into the building envelope to create clear sight lines around the entire door to maximise views and deliver excellent energy efficiency.



The door head is fully concealed into the building envelope to ensure clear glass sight lines right to the ceiling.

#### GENERAL

**Max Panel Height\***  
3300mm

**Max Panel Width\***  
2500mm

**Max Glass Thickness**  
26mm

**Frame Depth**  
Various

#### ENERGY

**UW Range**  
2.2-4.2

**SHGC Range**  
0.15-0.59

#### WEATHER

**Maximum Water**  
300Pa

#### ACOUSTICS

