


### KEY FEATURES

- Top hung with a sill that complies with AS1428 access and mobility standard - gap less than or equal to 13mm,
- The custom Centor E3 quad rollers are fully adjustable up and down when doors are in the frame.
- Tested for compliance with the relevant Standards.
- The extra strong multi hollow meeting stiles allow large sliding doors to be fabricated in high wind load areas, refer panel strength tables earlier in this Section.
- There are a large variety of door combinations (XF, FX, FXXF, XXF, FXX, FXXXXF and cavity sliding doors ).
- Compatible with Centor SIE screens up to 7500mm wide.
- Square clean lines with soft radius edges on internal meeting stile corners.




For the ultimate architectural look the 704T head can be recessed during installation for a minimal appearance.



The sill incorporates "Top Hat" feature which fills the recess in the sill to ensure disability access and minimise the risk of trips and falls - door panels glide over this rail.



Can be installed with a FlowTHRU™ drain for the ultimate flush threshold solution.



Doors run on heavy duty overhead rollers, delivering smooth, reliable operation

#### GENERAL

**Max Panel Height\***  
3300mm

**Max Panel Width\***  
2500mm

**Max Glass Thickness**  
24mm

**Frame Depth**  
Various

#### ENERGY

**UW Range**  
3.0-6.2

**SHGC Range**  
0.15-0.59

#### WEATHER

**Maximum Water**  
300 Pa. (35mm Sill)

450 Pa. (55mm Sill)

#### ACOUSTICS

**6.38mm Lam**  
30 (0;-1)

**10.38mm Lam**  
31 (-1;-1)

**10.5mm VLam Hush™**  
33 (0;-2)

