


### KEY FEATURES


- Architectural Sliding window with external sliding sash.
- Clean lines for improved visual appearance.
- There is a large variety of window combinations possible (SF, FS, SFS, FSF or FSSF).
- The window is compatible with the high performance Series 406 FrontGLAZE™ and Series 407 FaceLINE™ framing.
- The head and jamb sections have an additional weather leg to ensure that junctions between sliders and fixed sidelights/highlights maintain the high water resistance.
- Sliders fitted with mortice lock.
- Sashes run on heavy duty double bogey wheel carriages.
- Threshold and snap-in flat filler ensure that the clean looks are maintained.




Standard splayed or alternative square rails.



Heavy duty double bogey wheel assembly standard.



Designed to go into commercial sub-sill.



Custom mortice lock is standard. Lock can be fitted with ICON™ stainless steel cover plate or ANDO™ powder coated cast aluminium cover.

#### GENERAL

**Max Panel Height\***  
1600mm

**Max Panel Width\***  
1350mm

**Max Glass Thickness**  
24mm

**Frame Depth**  
N/A

#### ENERGY

**UW Range**

**SHGC Range**

#### WEATHER

**Maximum Water**  
600 Pa.

#### ACOUSTICS

This product has not been acoustics tested.



\*Dimensions subject to individual site conditions.